



HUB2 Hub and Bus Isolator

Features

- Divide the bus into two completely isolated outputs (if one output fails, the other will continue to function)
- One input port, 2 completely isolated output ports
- Each output port provides communications up to 900m (3000ft)



Siren set

- Metal Siren Box
- Internal Siren
- External Siren Horn
- Tamper Switch



Internal Siren

- 12V powered
- 15W Power, 110dB



External Siren Horn

- 12V powered
- 15W Power, 110dB





Strobe Light

- 12V powered
- Bright Flashing
- LED



SR130

Wireless Outdoor Siren with Built-in Strobe Light

The SR130 is a weatherproof (IP54) and fully supervised wireless siren with a built-in strobe light. SR130 provides fast response to alarm signals with differentiation between intrusion and fire events.

Features

- Battery operated (3 "C" alkaline batteries) Weather-resistant design with UV protection
- 2-way, fully supervised communication with the control panel
- 100dB Piezo siren
- Separate alarm notifications for intrusion and fire
- Dual-tamper detection (cover and wall)
- Squawk functionality
- Wireless range in a typical residential environment: Up to 70m (230 ft)
- Strobe lens available in 3 colors (red, blue, and amber)
- Fully powered using three 1.5 Vdc type "C" alkaline batteries (included)
- Signal strength/RF transmission and status LED
- Operating temperature: -25°C to 55°C (-13°F to 131°F)
- RF frequency: 433MHz or 868MHz
- Dimensions: 13.4cm x 21.17cm x 5.1cm (5.29in x 8.34in x 2.01 in)
- Compatible with MG5000 and MG5050 V4.0 or higher, MG5075, Spectra SP series V4.0 or higher (except SP4000) when using an RTX3 V1.5 or higher, as well as with MG6250 V3.0 and higher

